

Amendments to the Claims

This listing will replace all prior versions and listings of claims in the application:

Listing of Claims

1. (Cancelled)
2. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the ~~composition is an emulsion having an aqueous external phase wherein the viscosity is about 5000 cps to about 500,000 cps.~~
3. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the viscosity is about 50,000 cps to about 1,500,000 cps.
4. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the viscosity is about 100,000 cps to about 1,000,000 cps.
5. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the viscosity is about 250,000 cps to about 1,500,000 cps.
6. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the viscosity is about 20,000 cps to about 200,000 cps.
7. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the viscosity is about 35,000 cps to about 75,000 cps.

8. (Cancelled)

9. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the composition is maintained in the ~~sealed~~ container for a period of about 2 hours to about 24 hours after each use.

10. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the container is a jar.

11. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the container has an adjustable inner volume.

12. (Cancelled)

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)

16. (Cancelled)

17. (Cancelled)

18. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the ~~hydrofluoroether~~ one or more perfluorobutyl ethers is selected from the group consisting of methyl perfluorobutyl ether, methyl perfluoroisobutyl ether, ethyl perfluorobutyl ether, ethyl perfluoroisobutyl ether, and any combinations thereof.

19. (Cancelled)

20. (Cancelled)

21. (Cancelled)

22. (Cancelled)

23. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound has a vapor pressure about 100 mbar to about 300 mbar at 25 degrees C.

24. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound has a boiling point about 45 degrees C to about 85 ~~110~~ degrees C.

25. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound has a boiling point about 65 degrees C to about 85 degrees C.

26. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound is present in an amount about 0.01 wt% to about 25 wt% by total weight of the composition.

27. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound is present in an amount about 0.1 wt% to about 3 wt% by total weight of the composition.

28. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound is present in an amount about 0.2 wt% to about 1 wt% by total weight of the composition.

29. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound is present in an amount about 0.25 wt% to less than 0.5 wt% by total weight of the composition.

30. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein said volatile compound is present in an amount about 1 wt% to about 15 wt% by total weight of the composition.

31. (Currently amended) The ~~composition~~ system of claim ~~1~~ 38, wherein the volatile compound is present in an amount about 2.5 wt% to about 10 wt% by total weight of the composition.

32. (Cancelled)

33. (Currently amended) The ~~composition~~ system of claim ~~32~~ 18, wherein the ~~fluorocarbon compound is a hydrofluoroether~~ viscosity is about 5000 cps to about 500,000 cps.

34. (Currently amended) The ~~composition~~ method of claim ~~32~~ 40, wherein the ~~hydrofluoroether is present in an amount about 0.1 wt% to about 3 wt% by total weight of the composition~~ viscosity is about 5000 cps to about 500,000 cps.

35. (Currently amended) The ~~composition~~ method of claim ~~32~~ 40, wherein the hydrofluoroether is present in an amount about 0.25 wt% to less than 0.5 wt% by total weight of the composition.

36. (Cancelled)

37. (Currently amended) The ~~composition~~ method of claim ~~32~~ 40, wherein the composition is maintained in the ~~sealed~~ container for a period of about 2 hours to about 24 hours after each use.

38. (Currently amended) A system, comprising:

a non-aerosol container;

a cap, the cap being sealable with and removable from the container; and

a composition having a textured surface appearance and being situated within the container that builds up pressure when sealed and releases pressure when opened, the composition having a volatile compound in an amount effective to renew the textured surface appearance after the surface has been disturbed and after the container has been sealed against escape of pressure by the cap, the composition having a viscosity from about 20,000 cps to about 1,500,000 ~~2,500,000~~ cps, the composition being an emulsion having an oil phase and a water phase, the emulsion being an oil-in-water emulsion, the emulsion having an emulsifier,

wherein the volatile compound has a vapor pressure about 20 mbar to about 500 mbar at 25 degrees C and a boiling point from about 45 degrees C to about 85 degrees C, ~~and~~

wherein the volatile compound does not totally dissolve in either the oil phase or the water phase,

wherein the volatile compound has one or more perfluorobutyl ethers, and wherein the composition is in the form of a cream.

39. (Cancelled)

40. (Currently amended) A method of imparting a self-renewing and self-leveling textured surface appearance to a composition after each use, the composition having ~~at least one~~ a volatile compound with a vapor pressure from about 20 mbar to about 500 mbar at 25 degrees C and a boiling point from about 45 degrees C to about ~~110~~ 85 degrees C, the composition being an emulsion having an oil phase and a water phase, the volatile compound not totally dissolving in either the oil phase or the water phase, the emulsion being an oil-in-water emulsion, the

emulsion having an emulsifier, the volatile compound being one or more perfluorobutyl ethers, the composition being in the form of a cream, the composition having a viscosity of from about 20,000 cps to about 1,500,000 cps, comprising:

providing the composition in an amount effective for enabling such self-renewing and self-leveling appearance in a non-aerosol container having a removably sealable cap effective to seal the composition against escape of pressure, and

maintaining the composition in the container in a capped state for a pre-determined period of time after each use to allow the composition to self-renew and self-level the textured surface appearance of the composition.

41. (Currently amended) A method of leveling surface appearance of a cream composition after each use of the composition, the method comprising:

including in the composition a volatile compound having a vapor pressure from about 20 mbar to about 500 mbar and a boiling point from about 45 degrees C to about ~~110~~ 85 degrees C and providing the composition with a viscosity from about ~~100,000~~ 20,000 cps to about 1,500,000 cps, the composition being an emulsion having an oil phase and a water phase, the volatile compound not totally dissolving in either the oil phase or the water phase, the emulsion being an oil-in-water emulsion, the emulsion having an emulsifier, the volatile compound being one or more perfluorobutyl ethers, the composition being in the form of a cream; and

situating the composition in a non-aerosol container having a removable and sealable cap that seals against escape of pressure for a pre-determined period of time after each use,

wherein the surface appearance of the composition self-levels during such pre-determined period of time.